

EVDE25D4DUM

Delta DC Wallbox EV Charger 25kW Type CCS2 and CHAdeMO



Component type	Charging device E-Mobility
Range	DC Wallbox
Model	N/A
Product status	Existing

The Delta DC Chargers are strong and robust and ideal for fast charging in urban and rural environments. Air-cooled and steel cased they are durable, reliable and commercial grade. Connection to all third party cloud-based platforms via in-built modem and OCPP communication protocol. Offering split load options and CCS2-CCS2 or CCS2-CHAdeMO plug combinations, they suit all current EV types.

ELECTRICAL	Nominal connection power	25.0 kW
	Max. power per charging point	25.0 kW
COMMUNICATION	With load management	Yes
	With communication interface	Yes
	Function access control	Yes
CONSTRUCTION	Mounting method	Wall mounting
	Degree of protection (IP)	IP55
	Number of vehicle connectors Type 1	0.0
	Number of vehicle connectors Type 1 CCS	0.0
	Number of vehicle connectors Type 2	0.0
	Number of vehicle connectors Type 2 CCS	1.0
	Number of vehicle connectors CHAdeMO	1.0
	Emergency stop button	No
MECHANICAL	With display	Yes
	Impact strength	IK10
DIMENSIONS	Height	430.0 mm
	Depth	230.0 mm
	Width	680.0 mm
	Length of charging cable	4.0 m

EVDE25D4DUM

Delta DC Wallbox EV Charger 25kW Type CCS2 and CHAdeMO



RELATED PRODUCTS

ACCESSORY



Item No: EVPEBKT02

Required: No

Description: Delta DC EV Charger 25kW Free Standing Mount Post